

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 37578

TRANSELF NFJ 75W-80

Date of the previous version: 2016-11-23

Revision Date: 2016-12-27

Version 7.01

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	
Number	
Substance/mixture	

TRANSELF NFJ 75W-80 NQ7 Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Transmission fluid.

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71
	Fax: +33 (0)1 41 35 84 71

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.msds-lubs@total.com

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670 France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59 In France - Poison centers: ANGERS : 02 41 48 21 21 BORDEAUX : 05 56 96 40 80 LILLE : 08 00 59 59 59 LYON : 04 72 11 69 11 MARSEILLE : 04 91 75 25 25 NANCY : 03 83 22 50 50 PARIS : 01 40 05 48 48 STRASBOURG : 03 88 37 37 37 TOULOUSE : 05 61 77 74 47

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

Classification

The product is classified as dangerous in accordance with Regulation (EC) No. 1272/2008 Chronic aquatic toxicity - Category 3 - (H412)

2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008

Hazard Statements

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P273 - Avoid release to the environment P501 - Dispose of contents/ container to an approved waste disposal plant

Supplemental Hazard Statements

EUH208 - Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl; C14-18 alpha-olefin epoxide, reaction products with boric acid; Triphenyl phosphite May produce an allergic reaction

2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Chemical nature

The product is made from refined mineral base oils and synthetic oils .

Hazardous ingredients

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Distillates (petroleum), hydrotreated heavy paraffinic	265-157-1	01-2119484627-25	64742-54-7	50-<60	Asp. Tox. 1 (H304)
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	-	01-2119486452-34	68037-01-4	5-<10	Asp. Tox. 1 (H304)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	276-737-9	01-2119474878-16	72623-86-0	3-<5	Asp. Tox. 1 (H304)
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	224-235-5	01-2119493635-27	4259-15-8	1-<2.5	Aquatic Chronic 2 (H411) Eye Dam. 1 (H318)



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	931-384-6	01-2119493620-38	٨	1-<2.5	Acute Tox. 4 (H302) Aquatic Chronic 2 (H411) Eye Dam. 1 (H318) Skin Sens. 1 (H317)
C14-18 alpha-olefin epoxide, reaction products with boric acid	-	01-2119976364-28	٨	0.1-<1	Skin Sens. 1 (H317)
Triphenyl phosphite	202-908-4	no data available	101-02-0	0.1-<1	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Skin Sens. 1 (H317) Acute M factor = 1

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
4.2. Most important sympt	come and offects, both coute and delayed
<u>112</u> : most important sympt	oms and effects, both acute and delayed
Eye contact	Not classified. The supplier of some components contained within this formulation has indicated that the classification as irritant is not required.
	Not classified. The supplier of some components contained within this formulation has
Eye contact	Not classified. The supplier of some components contained within this formulation has indicated that the classification as irritant is not required. Not classified. May produce an allergic reaction. Repeated or prolonged skin contact may



TRANSELF NFJ 75W-80

	Revision Date: 2016-12-27	Version 7.01
4.3. Indication of any imm	ediate medical attention and special treatment needed	
Notes to physician	Treat symptomatically.	
Section 5: FIRE-FIGHTING N	MEASURES	
5.1. Extinguishing media		
Suitable Extinguishing Media	Carbon dioxide (CO ₂). ABC powder. Foam. Water spray or fog.	
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.	
5.2. Special hazards arisin	g from the substance or mixture	
Special Hazard	Incomplete combustion and thermolysis produces potentially toxic gases su monoxide and carbon dioxide, Sulfur oxides, Phosphorous oxides, Nitrogen Zinc oxides, Mercaptans, Hydrogen sulphide.	
5.3. Advice for fire-fighters	<u>8</u>	
Special protective equipment for fire-fighters	Wear self-contained breathing apparatus and protective suit.	
Other information	Cool containers / tanks with water spray. Fire residues and contaminated fir water must be disposed of in accordance with local regulations.	e extinguishing
Section 6: ACCIDENTAL RE	LEASE MEASURES	

6.1. Personal precautions, protective equipment and emergency procedures

General Information	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according
	to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4. Reference to other sections



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

Personal Protective Equipment	See Section 8 for more detail.
Waste treatment	See section 13.
Section 7: HANDLING AND	STORAGE
7.1. Precautions for safe	handling
Advice on safe handling	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.
7.2. Conditions for safe st	torage, including any incompatibilities
Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all
	indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
Materials to Avoid	indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical
	indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
Materials to Avoid	indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
Materials to Avoid 7.3. Specific end uses Specific use(s)	indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture. Strong oxidizing agents.
Materials to Avoid 7.3. Specific end uses Specific use(s)	 indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture. Strong oxidizing agents. No information available.
Materials to Avoid 7.3. Specific end uses Specific use(s) Section 8: EXPOSURE CON	 indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture. Strong oxidizing agents. No information available.

DNEL Worker (Industrial/Professional)

Chemical Name	Short term, systemic	Short term, local effects	Long term, systemic	Long term, local effects
	effects		effects	



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

				5.4 mg/m ³ /8h (aerosol -
Distillates (petroleum), hydrotreated heavy				inhalation)
paraffinic				initialationy
64742-54-7				
Lubricating oils				5.4 mg/m ³ /8h (aerosol -
(petroleum), C15-30,				inhalation)
hydrotreated neutral				in teleation ly
oil-based				
72623-86-0				
zinc			9.6 mg/kg bw/day Dermal	
bis[O,O-bis(2-ethylhexyl)]			6.6 mg/m ³ Inhalation	
bis(dithiophosphate)			olo ing/in initialation	
4259-15-8				
Reaction products of			12.5 mg/kg/8h (dermal)	
4-methyl-2-pentanol and			8.56 mg/m ³ /8h	
diphosphorus			(inhalation)	
pentasulfide,			(ECHA CHEM)	
propoxylated, esterified				
with diphosphorus				
pentaoxide, and salted by				
amines, C12-14-				
tert-alkyl				
C14-18 alpha-olefin			5.88 mg/m ³ Inhalation	
epoxide, reaction			16.7 mg/kg bw/day	
products with boric acid			Dermal	
^			2 011101	
Triphenyl phosphite		0.0117 mg/cm2 Dermal	0.3 mg/kg bw/day Dermal	0.0117 mg/cm2 Dermal
101-02-0			1.06 mg/m ³ Inhalation	
DNEL Consumer				
Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum),	enecta		enects	$1.0 m g/m^3/24h$
				1.2 mg/m ³ /24h (aerosol -
hydrotreated heavy				inhalation)
paraffinic				
paraffinic 64742-54-7				inhalation)
paraffinic 64742-54-7 Lubricating oils				inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30,				inhalation)
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral				inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based				inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0			4.8 mg/kg bw/dav Dermal	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc			4.8 mg/kg bw/day Dermal 1.67 mg/m³ Inhalation	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)]			1.67 mg/m ³ Inhalation	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)				inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8			1.67 mg/m ³ Inhalation 0.19 mg/kg/bw/day Oral	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8 Reaction products of			1.67 mg/m ³ Inhalation 0.19 mg/kg/bw/day Oral 6.25 mg/kg/24h (dermal)	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8 Reaction products of 4-methyl-2-pentanol and			1.67 mg/m ³ Inhalation 0.19 mg/kg/bw/day Oral 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8 Reaction products of 4-methyl-2-pentanol and diphosphorus			1.67 mg/m ³ Inhalation 0.19 mg/kg/bw/day Oral 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation)	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide,			1.67 mg/m ³ Inhalation 0.19 mg/kg/bw/day Oral 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation) 0.25 mg/kg/24h (oral)	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified			1.67 mg/m ³ Inhalation 0.19 mg/kg/bw/day Oral 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation)	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus			1.67 mg/m ³ Inhalation 0.19 mg/kg/bw/day Oral 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation) 0.25 mg/kg/24h (oral)	inhalation) 1.2 mg/m³/24h (inhalation
paraffinic 64742-54-7 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified			1.67 mg/m ³ Inhalation 0.19 mg/kg/bw/day Oral 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation) 0.25 mg/kg/24h (oral)	inhalation) 1.2 mg/m³/24h (inhalation



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

tert-alkyl			
C14-18 alpha-olefin epoxide, reaction products with boric acid		1.45 mg/m³ Inhalation 8.3 mg/kg bw/day Dermal 0.83 mg/kg bw/day Oral	
Triphenyl phosphite 101-02-0	0.0117 mg/cm2 Dermal	0.15 mg/kg bw/day Dermal 0.53 mg/m ³ Inhalation 0.075 mg/kg bw/day Oral	0.0117 mg/cm2 Dermal

Predicted No Effect Concentration Predicted No Effect Concentration (PNEC) (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
zinc bis[O,O-bis(2-ethylh exyl)] bis(dithiophosphate) 4259-15-8	0.044 mg/l ir	0.0701 mg/kg dw fw 0.00701 mg/kg dw mw	0.0548 mg/kg dw		3.8 mg/l	8.33 mg/kg food
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl ^	0.0012 mg/l fw 0.00012 mg/l mw 0.064 mg/ or	3.13 mg/kg fw 0.313 mg/kg mw	2.54 mg/kg soil dw		24.33 mg/l	10 mg/kg food
C14-18 alpha-olefin epoxide, reaction products with boric acid ^	0.2 mg/l fw 0.02 mg/l mw 1 mg/l or	8556 mg/kg dw fw 855.6 mg/kg dw mw	1706.3 mg/kg dw		100 mg/l	33.3 mg/kg food

8.2. Exposure controls

Occupational Exposure Controls

Engineering MeasuresApply technical measures to comply with the occupational exposure limits. Ensure
adequate ventilation, especially in confined areas. When working in confined spaces (tanks,
containers, etc.), ensure that there is a supply of air suitable for breathing and wear the
recommended equipment.***Personal Protective EquipmentProtective engineering solutions should be implemented and in use before personal
protective equipment is considered. The personal protective equipment (PPE)
recommendations apply to the product ITSELF. In case of mixtures or formulations, it is
suggested that you contact the relevant PPE suppliers.***Respiratory protectionNone under normal use conditions. When workers are facing concentrations above the



SDS # : 37578	TRANSELF NFJ 75W-80			
	Revision Date: 2016-12-27	Version 7.01		
	exposure limit they must use appropriate certified respirators. Resp filter for vapour/particulate (EN 14387), Type A/P1. The use of brea comply strictly with the manufacturer's instructions and the regulati choices and uses.***	athing apparatus must		
Eye Protection	If splashes are likely to occur, wear:. Safety glasses with side-shiel	ds.***		
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long	sleeved clothing.		
Hand Protection	Hydrocarbon-proof gloves, Fluorinated rubber. Nitrile rubber. In case of prolonged con with the product, it is recommended to wear gloves complying with EN 420 and EN 37 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at le These values are indicative only. The level of protection is provided by the material of glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructi regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product used, such as the danger of cuts, abrasion, and the contact time.***			

Environmental exposure controls

General Information

The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Color Physical State @20°C Odor Odor Threshold		limpid To slightly cloudy amber liquid Characteristic No information available	
<u>Property</u> pH Melting point/range	<u>Values</u>	<u>Remarks</u> Not applicable Not applicable	<u>Method</u>
Boiling point/boiling range		No information available	
Flash point	> 200 °C > 392 °F		
Evaporation rate Flammability Limits in Air		No information available No information available	
upper Lower Vapor Pressure Vapor density Relative density	0.874 - 0.884	No information available No information available No information available No information available @ 15 °C	ISO 12185



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

Density Water solubility Solubility in other solvents logPow Autoignition temperature Decomposition temperature Viscosity, kinematic Explosive properties Oxidizing Properties Possibility of hazardous reactions	874 - 884 kg/m ³ 43.0 - 49.0 mm2/s 8.60 - 9.0 mm2/s Not explosive Not applicable No information available	 @ 15 °C Insoluble No information available No information available No information available @ 40 °C @ 100 °C 	ISO 12185 ISO 3104 ISO 3104
9.2. Other information			
Freezing Point		No information available	
Section 10: STABILITY AND	REACTIVITY		
10.1. Reactivity			
General Information	No information available.		
10.2. Chemical stability			
Stability	Stable under recommend	led storage conditions.	
10.3. Possibility of hazardo	ous reactions		
Hazardous Reactions	None under normal proce	essing.	
10.4. Conditions to Avoid			
Conditions to Avoid	Heat (temperatures abov	e flash point), sparks, ignition	points, flames, static electricity.
10.5. Incompatible materia	<u>als</u>		
Materials to Avoid	Strong oxidizing agents.		
10.6. Hazardous Decompos	sition Products		
Hazardous Decomposition Product			hermolysis may produce gases of ide, various hydrocarbons, aldehydes
Section 11: TOXICOLOGICA	L INFORMATION		
11.1. Information on toxico	ological effects		

Acute toxicity Local effects Product Information



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

Skin contact Eye contact Inhalation Ingestion	 Not classified. May produce an allergic reaction. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Not classified. The supplier of some components contained within this formulation has indicated that the classification as irritant is not required. Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
ATEmix (oral)	7,434.00 mg/kg
ATEmix (dermal)	6,994.00 mg/kg
ATEmix (inhalation-gas)	> 5,000.00
ATEmix (inhalation-dust/mist)	7.20 mg/l
ATEmix (inhalation-vapor)	197.50 mg/l

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy	LD50 > 5000 mg/kg bw (rat -	5 5 1	LC50 (4h) > 5 mg/l (aerosol) (rat -
paraffinic	OECD 420)	OECD 402)	OECD 403)
Dec-1-ene, homopolymer, hydrogenated	LD50 > 5000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rat)	LC50 (4h) > 5.2 mg/l (Rat)
Dec-1-ene, oligomers, hydrogenated			
Lubricating oils (petroleum), C15-30,	LD50 > 5000 mg/kg bw (Rat -	LD50 > 2000 mg/kg (Rabbit -	LD50 (4h) > 5.53 mg/l (Rat -
hydrotreated neutral oil-based	OECD TG 401)	OECD 402)	OECD 403)
zinc bis[O,O-bis(2-ethylhexyl)]	LD50 3100 mg/kg (Rat - OECD	LD50 > 5000 mg/kg (Rabbit -	
bis(dithiophosphate)	401)	OECD 402)	
Reaction products of 4-methyl-2-pentanol	LD50 2000 mg/kg bw (Rat -		-
and diphosphorus pentasulfide,	OECD TG 401)		
propoxylated, esterified with diphosphorus			
pentaoxide, and salted by amines, C12-14-			
tert-alkyl			
C14-18 alpha-olefin epoxide, reaction	LD50 > 16000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rat - OECD	
products with boric acid		402)	
Triphenyl phosphite	LD50 1590 mg/kg (Rat - OECD	> 2000 mg/kg (Rabbit) = 1180	LC50 (1h) > 6.7 mg/l (Rat -
	401)	mg/kg (Rat)	aerosol - OECD 403)

Sensitization

Sensitization

Not classified as a sensitizer. Contains sensitizer(s). May produce an allergic reaction. The supplier of one of the components contained within this formulation has indicated that they have data, which confirms that at the concentration used, no sensitisation classification is required .

This product does not present any known or suspected reproductive hazards.

Specific effects

Carcinogenicity Mutagenicity Reproductive toxicity

Repeated Dose Toxicity

Subchronic toxicity

No information available.

This product is not classified carcinogenic.

This product is not classified as mutagenic.

Target Organ Effects (STOT)



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

Other information

Other adverse effects (

Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated 68037-01-4	EL50 (72h) > 1000 mg/l (Scenedesmus capricornutum - OECD 201)	EC50 (48h) 190 mg/l (Daphnia magna) LE50(48h) > 1000 mg/l (Daphnia magna)	LC50(96h) > 750 mg/l (Pimephales promelas) LL50(96h) > 1000 mg/l (Pimephales promelas)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0		EL50 (48h) > 10000 mg/l (OECD TG 202)	LL50 (96h) > 100 mg/l (OECD TG 203)	
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) 4259-15-8	EC50 (72h) > 240 mg/L (Desmodesmus subspicatus)	EC50 (48h) > 1 - < 10 mg/L (Daphnia magna - OECD 202)	LC50 (96h) > 1 - 2 mg/L (Oncorhynchus mykiss - OECD 203)	
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl ^	EL50 (96h) > 15 mg (Selenastrum capricornutum - OECD 201) EC50 (96h) 6.4 mg/l (Pseudokirchnerella subcapitata - OECD 201) EC50 (96h) 15 mg/l (Pseudokirchnerella subcapitata - OECD 201) EC50 (96h) 6.4 mg/L (Selenastrum capricornutum- OECD TG 201) (ECHA CHEM)	EL50 (48h) ca. 91.4 mg/l (Daphnia magna - OECD 202)	LL50 (96h) ca. 24 mg/l (Oncorhynchus mykiss - OECD 203)	
C14-18 alpha-olefin epoxide, reaction products with boric acid ^	EL50 (72h) > 100 mg/l (Pseudokirchnerella subcapitata - static - OECD 201)	EL50 (48h) >= 100 mg/l (Daphnia magna - static - OECD 202)	LL50 (96h) > 100 m/l (Oncorhynchus mykiss - semi static - OECD 203)	
Triphenyl phosphite 101-02-0		EC50(48h) 0.94 mg/l (Cladocère)		



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

<u>Chronic aquatic toxicity</u> - Product Information No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated 68037-01-4	NOELR (72h) 1000 mg/l (Scenedesmus capricornutum - OECD 201)	NOELR (21d) 125 mg/l (Daphnia magna - OECD 211)		
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0		NOEL (21d) = 10 mg/l (OECD TG 202)	NOELR (14d) > 1000 mg/l (QSAR modelled data)	
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl ^	NOEC (96h) 1.7 mg/l (Pseudokirchnerella subcapitata - OECD 201) par NOEC (96h) 3.3 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (21d) 0.91 mg/l (Daphnia magna - OECD 211) NOEL (21d) 0.12 mg/l (Daphnia magna - OECD 211) EL50 (21d) 0.66 mg/l (Daphnia magna - OECD 211)	-	EC50 (3h) ca. 2433 mg/L (Activated Sludge, domestic - OECD TG 209) (ECHA CHEM)

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

No information available.

logPow Component Information

No information available

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic - 64742-54-7	-
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based - 72623-86-0	6.1
. 2020 00 0	0.50
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) - 4259-15-8	3.59
Reaction products of 4-methyl-2-pentanol and diphosphorus	< 0.30 to >7.10 (OECD TG 117) (ECHA CHEM)
pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and	
salted by amines, C12-14- tert-alkyl - ^	
Triphenyl phosphite - 101-02-0	6.62



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

12.4. Mobility in soil

SoilGiven its physical and chemical characteristics, the product generally shows low soil
mobility.AirLoss by evaporation is limited.WaterInsoluble. The product spreads on the surface of the water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

General Information

No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products	Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EWC Waste Disposal No.	The following Waste Codes are only suggestions: 13 02 05, According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

ADR/RID	Not regulated
IMDG/IMO	Not regulated
ICAO/IATA	Not regulated
ADN	Not regulated

Section 15: REGULATORY INFORMATION



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment

No information available

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed

- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H319 Causes serious eye irritation
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects
- H411 Toxic to aquatic life with long lasting effects

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

- bw = body weight
- bw/day = body weight/day
- EC x = Effect Concentration associated with x% response
- GLP = Good Laboratory Practice
- IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

- LD50 = 50% Lethal Dose Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading
- NIOSH = National Institute of Occupational Safety and Health
- NOAEL = No Observed Adverse Effect Level
- NOEC = No Observed Effect Concentration
- NOEL = No Observed Effect Level
- OECD = Organization for Economic Co-operation and Development
- OSHA = Occupational Safety and Health Administration
- UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material
- DNEL = Derived No Effect Level
- PNEC = Predicted No Effect Concentration
- dw = dry weight
- fw = fresh water



TRANSELF NFJ 75W-80

Revision Date: 2016-12-27

Version 7.01

mw = marine water or = occasional release

Legend Section 8

TWA: Time	Weight Average		
STEL: Shor	t Time Exposure Limit		
	ssible exposure limit		
	nmended exposure limit		
	nold Limit Values		
+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date:2016-12-27Revision Note*** Indicates updated section.This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet