

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS #: 32654 ELFMATIC G 3 SYN

Date of the previous version: 2016-02-23 Revision Date: 2016-12-29 Version 2.02

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE

COMPANY/UNDERTAKING

1.1. Product identifier

Product name ELFMATIC G 3 SYN

NumberFUDSubstance/mixtureMixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Transmission fluid.

1.3. Details of the supplier of the safety data sheet

Supplier TOTAL LUBRIFIANTS

562 Avenue du Parc de L'ile 92029 Nanterre Cedex

FRANCE

Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

For further information, please contact:

Contact Point HSE

E-mail Address rm.msds-lubs@total.com

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670

France - ORFILA (INRS) Tél: +33 (0)1 45 42 59 59

In France - Poison centers:
ANGERS: 02 41 48 21 21
BORDEAUX: 05 56 96 40 80
LILLE: 08 00 59 59 59
LYON: 04 72 11 69 11
MARSEILLE: 04 91 75 25 25
NANCY: 03 83 22 50 50
PARIS: 01 40 05 48 48

STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008



ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008

2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008

Hazard Statements

None

Precautionary Statements

None**

Supplemental Hazard Statements

EUH210 - Safety data sheet available on request***

Contains Alkoxylated long chain alkylamine May produce an allergic reaction

2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Hazardous ingredients

iazaraous irigi calcints					
Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Distillates (petroleum), hydrotreated heavy paraffinic***	265-157-1***	01-2119484627-25	64742-54-7	40-<50	Asp. Tox. 1 (H304)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	265-169-7***	01-2119471299-27	64742-65-0	<10	-

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR



ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids.

Skin contact Remove contaminated clothing and shoes. Wash off with soap and water. Wash

contaminated clothing before reuse.

Inhalation Move to fresh air.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or Poison Control Center immediately.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact Not classified.

Skin contact Not classified. May produce an allergic reaction.

Inhalation Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory

system.

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media Carbon dioxide (CO 2). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may

be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Advice for fire-fighters

Special protective equipment for

fire-fighters

Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing

water must be disposed of in accordance with local regulations.



ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from

entering drains or water courses. Local authorities should be advised if significant spillages

cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g.

sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for

disposal.

6.4. Reference to other sections

See Section 8 for more detail. **Personal Protective Equipment**

See section 13. Waste treatment

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

When using, do not eat, drink or smoke. For personal protection see section 8. Use only in Advice on safe handling

well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes

and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges: Ground/bond containers, tanks

and transfer/receiving equipment.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

not use abrasives, solvents or fuels. Do not dry hands with rags that have been

contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical

Version FII



Materials to Avoid

ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

contacts. Protect from frost, heat and sunlight. Protect from moisture.

Strong oxidizing agents.

7.3. Specific end uses

Specific use(s) No information available.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH

(TLV) TWA 5 mg/m³ (highly refined)

Legend See section 16

DNEL Worker (Industrial/Professional)

DIVEL WORKER (III daotiia				
Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				5.4 mg/m³/8h (aerosol - inhalation)
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0				5.4 mg/m³/8h (aerosol - inhalation)

DNEL Consumer

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				1.2 mg/m ³ /24h (aerosol - inhalation)
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0				1.2 mg/m ³ /24h (aerosol - inhalation)

8.2. Exposure controls

Occupational Exposure Controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. When working in

confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for

breathing and wear the recommended equipment.

Personal Protective Equipment



SDS #: 32654 **ELFMATIC G 3 SYN**

> **Revision Date: 2016-12-29** Version 2.02

General Information If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Respiratory protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN

14387). Type A/P1. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Eye Protection If splashes are likely to occur, wear:. Safety glasses with side-shields.

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Skin and body protection

Hand Protection Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. Please observe the

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374,

contact the supplier of the EC approved gloves.

Environmental exposure controls

The product should not be allowed to enter drains, water courses or the soil. **General Information**

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance limpid red Color Physical State @20°C liquid Odor Characteristic

No information available **Odor Threshold**

Property Values Remarks Method Not applicable На Not applicable*** Melting point/range

No information available Boiling point/boiling range

Flash point 230 °C ISO 2592 446 °F ISO 2592

No information available **Evaporation rate** Flammability Limits in Air

No information available upper No information available

Lower No information available No information available **Vapor Pressure** Vapor density No information available

@ 15 °C Relative density 0.854 ISO 12185 Density 854 kg/m³ @ 15 °C ISO 12185

Insoluble Water solubility

Version FU



SDS #: 32654 ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

ISO 3104

ISO 3104

Solubility in other solvents Soluble in many common

organic solvents

logPowNo information availableAutoignition temperatureNo information availableDecomposition temperatureNo information available

35 - 38 mm2/s @ 40 °C

@ 100 °C

7.15 - 7.65 mm2/s **Explosive properties**Not explosive

Oxidizing Properties

Not applicable

Possibility of hazardous reactions No information available

9.2. Other information

Freezing Point No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Viscosity, kinematic

General Information No information available.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

10.5. Incompatible materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact . Not classified. May produce an allergic reaction.



SDS #: 32654 ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

Eye contact . Not classified.

Inhalation . Not classified. Inhalation of vapors in high concentration may cause irritation of

respiratory system.

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

 ATEmix (oral)
 11,788.00 mg/kg

 ATEmix (dermal)
 11,788.00 mg/kg

 ATEmix (inhalation-dust/mist)
 12.00 mg/l

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy	LD50 > 5000 mg/kg bw (rat -	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5 mg/l (aerosol) (rat -
paraffinic***	OECD 420)	OECD 402)	OECD 403)
Distillates (petroleum), solvent-dewaxed	LD50 > 5000 mg/kg bw (rat -	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5 mg/l (aerosol) (rat -
heavy paraffinic	OECD 420)	OECD 402)	OECD 403)

Sensitization

Sensitization Not classified as a sensitizer. Contains sensitizer(s). May produce an allergic reaction.

Specific effects

CarcinogenicityThis product is not classified carcinogenic. **Mutagenicity**This product is not classified as mutagenic.

Reproductive toxicityThis product does not present any known or suspected reproductive hazards.

Repeated Dose Toxicity

Subchronic toxicity No information available.

Target Organ Effects (STOT)

Other information

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and	Toxicity to fish	Toxicity to
	other aquatic invertebrates		microorganisms	



ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0	EL50 (72h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information .***

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic*** - 64742-54-7	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic - 64742-65-0	6.1

12.4. Mobility in soil

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility.

Air Loss by evaporation is limited.

Water Insoluble. The product spreads on the surface of the water.



ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

General Information No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products

Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EWC Waste Disposal No.

The following Waste Codes are only suggestions:. 13 02 05. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was

used.

Section 14: TRANSPORT INFORMATION

ADR/RID Not regulated

IMDG/IMO Not regulated

ICAO/IATA Not regulated

ADN Not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union



SDS #: 32654 ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water

mw = marine water

or = occasional release

Legend Section 8

TWA: Time Weight Average STEL: Short Time Exposure Limit PEL: Permissible exposure limit REL: Recommended exposure limit

TLV: Threshold Limit Values

+ Sensitizer * Skin designation

* Skin designation

* C: Carcinogen

M: Mutagen R: Toxic to reproduction

Revision Date: 2016-12-29

Revision Note*** Indicates updated section.



ELFMATIC G 3 SYN

Revision Date: 2016-12-29 Version 2.02

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet