

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 083350

TRANSMISSION AXLE 8 FE 75W-140

Date of the previous version: 201	6-09-30 Revision Date: 2016-12-29	Version 2.03
Section 1: IDENTIFICATION COMPANY/UNDERTAKING	I OF THE SUBSTANCE/MIXTURE AND OF THE	
1.1. Product identifier		
Product name Number Substance/mixture	TRANSMISSION AXLE 8 FE 75W-140 DGT Mixture	
1.2. Relevant identified us	es of the substance or mixture and uses advised again	<u>st</u>
Identified uses	Transmission fluid.	
1.3. Details of the supplie	of the safety data sheet	
Supplier	TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71	

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.msds-lubs@total.com

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670 France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59 In France - Poison centers: ANGERS : 02 41 48 21 21 BORDEAUX : 05 56 96 40 80 LILLE : 08 00 59 59 59 LYON : 04 72 11 69 11 MARSEILLE : 04 91 75 25 25 NANCY : 03 83 22 50 50 PARIS : 01 40 05 48 48 STRASBOURG : 03 88 37 37 37 TOULOUSE : 05 61 77 74 47

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

REGULATION (EC) No 1272/2008

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

Classification

The product is classified as dangerous in accordance with Regulation (EC) No. 1272/2008 Serious eye damage/eye irritation - Category 2 - (H319)

2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008



Signal Word WARNING

Hazard Statements H319 - Causes serious eye irritation

Precautionary Statements

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P280 - Wear eye protection/ face protection

EUH208 - Contains Polysulfides, di-tert-Bu; Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl May produce an allergic reaction

2.3. Other hazards

Physical-Chemical Properties	Contaminated surfaces will be extremely slippery.

Environmental properties

Should not be released into the environment.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Hazardous ingredients

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Hydrogenated dimerization	-	01-2119411393-49	٨	5-<10	Asp. Tox. 1 (H304)



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

products of 1-decene, 1-dodecene and 1-octene					Acute Tox. 4 (H332)
Polysulfides, di-tert-Bu	273-103-3	01-2119540515-43	68937-96-2	2.5-<5	Skin Sens. 1 (H317) Aquatic Chronic 3 (H412)
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	931-384-6	01-2119493620-38	۸	1-<2	Acute Tox. 4 (H302) Aquatic Chronic 2 (H411) Eye Dam. 1 (H318) Skin Sens. 1 (H317)
O,O,O-triphenyl phosphorothioate	209-909-9	no data available	597-82-0	0.3-<1	Repr. 2 (H361) Aquatic Chronic 4 (H413)

Additional information

The product is made from synthetic base oils (Polyalfaolefins) .

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
4.2. Most important sympto	oms and effects, both acute and delayed
Eye contact	Causes serious eye irritation.
Skin contact	Not classified. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
4.3. Indication of any imme	ediate medical attention and special treatment needed



TRANSMISSION AXLE 8 FE 75W-140

	Revision Date: 2016-12-29 Version 2.03
Notes to physician	Treat symptomatically.
Section 5: FIRE-FIGHTING	MEASURES
5.1. Extinguishing media	
Suitable Extinguishing Media	Foam. Carbon dioxide (CO 2). ABC powder. Water spray.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.
5.2. Special hazards arisin	ng from the substance or mixture
Special Hazard	Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide, Mercaptans, Hydrogen sulphide, Sulfur oxides, Nitrogen oxides (NOx), Phosphorous oxides.
5.3. Advice for fire-fighters	5
Special protective equipment for fire-fighters	Wear self-contained breathing apparatus and protective suit.
Other information	Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Section 6: ACCIDENTAL RE	LEASE MEASURES
6.1. Personal precautions,	protective equipment and emergency procedures
General Information	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Remove all sources of ignition.
6.2. Environmental precau	itions
General Information	Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained. Do not allow material to contaminate ground water system.
6.3. Methods and material	for containment and cleaning up
Methods for cleaning up	Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.
6.4. Reference to other se	ctions_
Personal Protective Equipment	See Section 8 for more detail.



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29 Version 2.03 See section 13. Waste treatment Section 7: HANDLING AND STORAGE 7.1. Precautions for safe handling Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. Take precautionary measures against static discharges. Ground/bond containers, tanks Prevention of fire and explosion and transfer/receiving equipment. Ensure the application of strict rules of hygiene by the personnel exposed to the risk of **Hygiene measures** contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. 7.2. Conditions for safe storage, including any incompatibilities **Technical measures/Storage** Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep conditions container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture. Materials to Avoid Strong oxidizing agents. 7.3. Specific end uses Specific use(s) No information available. Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION 8.1. Control parameters **Exposure limits** Do not contain substance with european workplace exposure limits in concentration above regulatory thresholds Legend See section 16

DNEL Worker (Industrial/Professional)

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Hydrogenated dimerization products of		3.9 mg/m ³ (inhalation)	22.9 mg/m ³ (inhalation)	



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

1-decene, 1-dodecene				
and 1-octene				
^				
Polysulfides, di-tert-Bu			14.5 mg/m ³ inhalation	
68937-96-2			3.3 mg/kg bw/day dermal	
Reaction products of			12.5 mg/kg/8h (dermal)	
4-methyl-2-pentanol and			8.56 mg/m ³ /8h	
diphosphorus			(inhalation)	
pentasulfide,			(ECHA CHEM)	
propoxylated, esterified				
with diphosphorus				
pentaoxide, and salted by				
amines, C12-14-				
tert-alkyl				
	L			
DNEL Consumer			· · · ·	
Chemical Name	Short term, systemic	Short term, local effects		Long term, local effects
	effects		effects	
Hydrogenated	16.8 mg/m ³ (inhalation)			3.9 mg/m ³ (inhalation)
dimerization products of				
1-decene, 1-dodecene				
and 1-octene				
^	1			
Polysulfides, di-tert-Bu			2.6 mg/m ³ inhalation	
Polysulfides, di-tert-Bu 68937-96-2	<u> </u>		2.6 mg/m³ inhalation 1.66 mg/kg bw/day	
			1.66 mg/kg bw/day dermal	
68937-96-2 Reaction products of			1.66 mg/kg bw/day dermal 6.25 mg/kg/24h (dermal)	
68937-96-2 Reaction products of 4-methyl-2-pentanol and			1.66 mg/kg bw/day dermal	
68937-96-2 Reaction products of 4-methyl-2-pentanol and diphosphorus			1.66 mg/kg bw/day dermal 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation)	
68937-96-2 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide,			1.66 mg/kg bw/day dermal 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation) 0.25 mg/kg/24h (oral)	
68937-96-2 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified			1.66 mg/kg bw/day dermal 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation)	
68937-96-2 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus			1.66 mg/kg bw/day dermal 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation) 0.25 mg/kg/24h (oral)	
68937-96-2 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by			1.66 mg/kg bw/day dermal 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation) 0.25 mg/kg/24h (oral)	
68937-96-2 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-			1.66 mg/kg bw/day dermal 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation) 0.25 mg/kg/24h (oral)	
68937-96-2 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by			1.66 mg/kg bw/day dermal 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation) 0.25 mg/kg/24h (oral)	
68937-96-2 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl			1.66 mg/kg bw/day dermal 6.25 mg/kg/24h (dermal) 2.2 mg/m ³ /24h (inhalation) 0.25 mg/kg/24h (oral)	

(PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Polysulfides,	0.00024 mg/l fw	7589 mg/kg dw	1513 mg/kg dw		4.51 mg/l	
di-tert-Bu	0.000024 mg/l	fw				
68937-96-2	mw	758.9 mg/kg dw				
	0.0024 mg/l or	mw				
Reaction products	0.0012 mg/l fw	3.13 mg/kg fw	2.54 mg/kg soil		24.33 mg/l	10 mg/kg food
of	0.00012 mg/l mw	0.313 mg/kg mw	dw			
4-methyl-2-pentanol	0.064 mg/ or					
and diphosphorus	_					
pentasulfide,						
propoxylated,						
esterified with						



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

	I					
diphosphorus						
pentaoxide, and						
salted by amines,						
C12-14- tert-alkyl						
8.2. Exposure	controls					
	controls					
Occupational Expo	sure Controls					
Engineering Measu	res	Apply technical me confined spaces (t breathing and wea	anks, containers, e	etc.), ensure that th		0
Personal Protective	Equipment					
General Informa	ation	ion If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supp				
Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/part 14387). Type A/P2. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.				our/particulate (EN vith the		
Eye Protection		If splashes are like	ely to occur, wear:.	Safety glasses wit	h side-shields.	
Skin and body p	protection	Wear suitable protective clothing. Protective gloves. Protective shoes or boots. Long sleeved clothing.				oots. Long
Hand Protectior	1	Hydrocarbon-proo with the product, it standards, protect These values are i glove, its technical appropriateness o	is recommended to ing at least for 480 indicative only. The characteristics, its	to wear gloves con minutes and havir e level of protection resistance to the	nplying with EN 42 ng a thickness of 0 n is provided by the chemicals to be ha	0 and EN 374 ,38 mm at least. e material of the

Environmental exposure controls

General Information

The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Color Physical State @20°C Odor Odor Threshold limpid yellow liquid Characteristic No information available



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

<u>Property</u> pH	<u>Values</u>	<u>Remarks</u> Not applicable	<u>Method</u>	
Melting point/range		Not applicable		
Boiling point/boiling range		No information available		
Flash point	> 200 °C > 392 °F		ASTM D 93 ASTM D 93	
Evaporation rate Flammability Limits in Air		No information available No information available		
upper Lower Vapor Pressure Vapor density Relative density Density Water solubility Solubility in other solvents	0.885 885 kg/m³	No information available No information available No information available No information available @ 15 °C @ 15 °C Insoluble Soluble in many common organic solvents		
logPow Autoignition temperature Decomposition temperature Viscosity, kinematic	27 mm2/s	No information available No information available No information available @ 100 °C		
Explosive properties Oxidizing Properties Possibility of hazardous reactions	Not explosive Not applicable No information available			
9.2. Other information				
Freezing Point		No information available		
Pour point	< -33 °C		ASTM D 97	
Section 10: STABILITY AND) REACTIVITY			
10.1. Reactivity				
General Information	No information available.			
10.2. Chemical stability				
Stability	Stable under recommend	ded storage conditions.		
10.3. Possibility of hazardo	ous reactions			
Hazardous Reactions	None under normal proce	essing.		
10.4. Conditions to Avoid				
				Version EU



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

10.5. Incompatible materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use. Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact	. Not classified. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Eye contact	. Causes serious eye irritation.
Inhalation	. Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
ATEmix (oral)	9,136.00 mg/kg
ATEmix (dermal)	9,201.00 mg/kg
ATEmix (inhalation-dust/mist)	7.50 mg/l
ATEmix (inhalation-vapor)	162.30 mg/l

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hydrogenated dimerization products of	LD50 >5000 mg/kg bw (rat-OECD	LD50 >2000 mg/kg bw (rat-OECD	LC50 (4h) 1170 mg/m ³ (aerosol
1-decene, 1-dodecene and 1-octene	401)	402)	rat-OECD 403)
			LC50 (4h) 1400 - 2000 mg/m ³
			(aerosol rat-OECD 403)
			LC50 (4h) 900 - 1400 mg/m ³
			(aerosol rat-OECD 403)
Reaction products of 4-methyl-2-pentanol	LD50 2000 mg/kg bw (Rat -		-
and diphosphorus pentasulfide,	OECD TG 401)		
propoxylated, esterified with diphosphorus			
pentaoxide, and salted by amines, C12-14-			
tert-alkyl			

Sensitization

Sensitization

Not classified as a sensitizer. The supplier of one of the components contained within this formulation has indicated that they have data, which confirms that at the concentration used, no sensitisation classification is required . Contains sensitizer(s). May produce an



TRANSMISSION AXLE 8 FE 75W-140

	Revision Date: 2016-12-29		Version 2.03
	allergic reaction.		
Specific effects			
Carcinogenicity	This product is not classif	ied carcinogenic.	
Mutagenicity	This product is not classif	ied as mutagenic.	
Reproductive toxicity	Contains a known or suspected reproductive toxin.		
Chemical Na		European Union	
O,O,O-triphenyl phos 597-82-0		Repr. 2 (H361)	
Repeated Dose Toxicity			
Subchronic toxicity	No information available.		
Target Organ Effects (STOT)			
Target Organ Effects (STOT)	No information available.		
Other information			
Other adverse effects	Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).		
Section 12: ECOLOGICAL I	NFORMATION		
12.1. Toxicity			

Not classified.

Acute aquatic toxicity - Product Information

No experimental data available .

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Hydrogenated dimerization products of 1-decene, 1-dodecene and 1-octene ^	EL50 (72h) > 1000 mg/l (Selenastrum capricornutum)	LL50 (96h) > 5056 mg/l (Americamysis bahia) EL50 (48h) >1000 mg/l (Daphnia magna)	EL50 (96h) >1000 mg/l (Pseudokirchneriella subcapitata) LL50 (96h) >1000 mg/l (Oncorhynchus mykiss) LL50 (96h) >5003 mg/l (Cyprinodon variegatus - OECD 203)	
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines,	EL50 (96h) > 15 mg (Selenastrum capricornutum - OECD 201) EC50 (96h) 6.4 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) ca. 91.4 mg/l (Daphnia magna - OECD 202)	LL50 (96h) ca. 24 mg/l (Oncorhynchus mykiss - OECD 203)	



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

Page 11/14

C12-14- tert-alkyl	EC50 (96h) 15 mg/l		
^	(Pseudokirchnerella		
	subcapitata - OECD 201)		
	EC50 (96h) 6.4 mg/L		
	(Selenastrum		
	capricornutum- OECD TG		
	201) (ECHA CHEM)		

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Hydrogenated dimerization products of 1-decene, 1-dodecene and 1-octene ^		EL50 (21d) > 1000 mg/l (Daphnia magna - OECD 211) LL50 (21d) > 1000 mg/l (Daphnia magna - OECD 211) NOEL (21d) 1000 mg/l (Daphnia magna - OECD 211) NOELR (21d) > 1000 mg/l (Daphnia magna)	NOEL (96h) >5003 mg/l (Cyprinodon variegatus - OECD 203)	
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl ^	NOEC (96h) 1.7 mg/l (Pseudokirchnerella subcapitata - OECD 201) par NOEC (96h) 3.3 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (21d) 0.91 mg/l (Daphnia magna - OECD 211) NOEL (21d) 0.12 mg/l (Daphnia magna - OECD 211) EL50 (21d) 0.66 mg/l (Daphnia magna - OECD 211)	-	EC50 (3h) ca. 2433 mg/L (Activated Sludge, domestic - OECD TG 209) (ECHA CHEM)

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

No information available.

logPow

No information available

Component Information

Chemical Name	log Pow
Polysulfides, di-tert-Bu - 68937-96-2	6



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl - ^		< 0.30 to >7.10 (OECD TG 117) (ECHA CHEM)	
12.4. Mobility in soil			
Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.		
Air	Loss by evaporation is limit	Loss by evaporation is limited.	
Water	Insoluble. The product spreads on the surface of the water.		
12.5. Results of PBT and vPvB assessment			
PBT and vPvB assessment	T and vPvB assessment No information available.		
12.6. Other adverse effects			
General Information	neral Information No information available.		
Section 13: DISPOSAL CONSIDERATIONS			

13.1. Waste treatment methods

Waste from Residues / Unused Products	Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EWC Waste Disposal No.	The following Waste Codes are only suggestions:. 13 02 06.
Other information	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION

ADR/RID_	Not regulated
IMDG/IMO	Not regulated
ICAO/IATA	Not regulated



ADN

TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

Not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment

No information available

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor

- H302 Harmful if swallowed
- H304 May be fatal if swallowed and enters airways
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H332 Harmful if inhaled
- H361 Suspected of damaging fertility or the unborn child if inhaled
- H411 Toxic to aquatic life with long lasting effects
- H412 Harmful to aquatic life with long lasting effects
- H413 May cause long lasting harmful effects to aquatic life

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

- NOEC = No Observed Effect Concentration
- NOEL = No Observed Effect Level



TRANSMISSION AXLE 8 FE 75W-140

Revision Date: 2016-12-29

Version 2.03

OECD = Organization for Economic Co-operation and Development OSHA = Occupational Safety and Health Administration UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material DNEL = Derived No Effect Level PNEC = Predicted No Effect Concentration dw = dry weight fw = fresh water mw = marine water or = occasional release Legend Section 8 TWA: Time Weight Average STEL: Short Time Exposure Limit PEL: Permissible exposure limit **REL:** Recommended exposure limit TLV: Threshold Limit Values Sensitizer Skin designation + ** Hazard Designation C: Carcinogen M: Mutagen R: Toxic to reproduction

 Revision Date:
 2016-12-29

 Revision Note
 *** Indicates updated section.

 This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet