Established: October 29, 2012 Revised: November 8, 2022

SAFETY DATA SHEET

SECTION 1. Identification

Product identifier:

Product name: Verity BIKE FS HR Ver3 10W-40 MA

4cycle gasoline engine oil for BIKE

Company Identification: Sanwa Kasei Kogyo Co. Ltd.

Address: Toshin 24 building, 2-20-5, Minamisaiwai, Nishi-ku,

Yokohama 220-0005, Japan

Product Information: Sales Department(Yokohama office)

Tel. +81-45-412-3161, Fax +81-45-412-3160

Health Emergency: Product Assurance Department

Tel. +81-45-778-2390, Fax. +81-45-778-2372

Business Hours: 9:00am-5:00pm (Monday - Friday)

Product No. 228329

SECTION 2. Hazard identification

GHS label elements, including precautionary statements

Physical Hazard: Flammable liquid: Not Classified

Health Hazard: No need for classification according to GHS criteria for this product.

Hazard Symbol No symbol

Signal word No signal word

Hazard Statement None

Precautionary statement

[Prevention] None[Response] None[Storage] None[Disposal] None

Even when there is no statement in notes by GHS classification, please refer to the following information about the safety measures / emergency measure / storage / abandonment of a product.

SECTION 3. Composition/information on ingredients

Substance or mixture Mixture

Chemical Name: Petroleum hydrocarbon and additives

Composition: Base oil Synthetic hydrocabon 70~80 %mass

Synthetic ester 1~9.9 %mass
Mineral oil 1~9.9 %mass

(Highly refined mineral oil contains <3%DMSO-extract, according to IP346)

Additive 1~9.9 %mass

SECTION 4. First-aid measures

Inhalation: IF INHALED:Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

Cover the body with blankets to keep warm and guiet. If you feel unwell, seek

medical advice.

Skin Contact: Immediately flush skin with large amount of water.

Wash contaminated clothing before reuse.

If skin irritation occurs: Get medical advice/attention.

Eye Contact: Rinse with clean water carefully for several minutes. Remove contact lenses

if present and if removal is easy, then continue rinsing. Rinse for 15 minutes at a

minimum and seek medical attention.

Ingestion: Do not induce vomiting. Drink (one glass) (two glass) of water.

Call a physician (or poison control center) immediately.

SECTION 5. Fire-fighting measures

Suitable Extinguishing Media: Mist of loaded liquid, dry chemicals, carbon dioxide, fire foam, and

dry sand are effective.

Extinguishing Media to Avoid: Use of straight steam of water can cause a risk of spreading fire.

Specific hazards arising from

the chemical:

In some cases of fire, may release irritant gases.

Fire Fighting: When burnt, may generate carbon monoxide and other toxic gases.

Spray water to the surrounding facilities for cooling.

Keep unauthorized persons off the site of occurrence of fire and

the surroundings.

Even after extinction, cool containers thoroughly with plenty of water.

Special protective equipment

Wear fire / flame resistant / retardant clothing.

and precautions for fire fighters: Fight fire from windward direction while wearing protective equipment.

If contact with skin is expected, wear impervious protective equipment

and gloves.

Use air-breathing apparatus and protective clothing whenever necessary.

SECTION 6. Accidental release measures

Personal precautions, protective Wear protective equipment when working.

equipment and emergency Remove nearly potential ignition sources immediately.

procedures: When mist is generated, use respiratory equipment to prevent inhalation

of mist.

Do not touch or walk through spillage.

Pay attention to the site of spillage, which is slippery.

Prevent spreading of oil spill with earth and sand, sandbags, or other Environmental precautions:

proper materials and use care not to allow the oil spill to flow to street

drains, sewer systems, and rivers.

At sea, install oil spill containment booms to prevent spreading of spills

and absorb with absorption mat or other materials.

Method and materials for In case of spillage in small quantity, collect spillage by absorbing with

containment and cleaning up: earth, sand, sawdust, waste, or other proper materials. In case of spillage enlarge quantity, enclose with embankment to prevent

spreading of spillage and collect spillage in empty containers to the

extent possible.

Prevention of second accident: Incase of spillage, immediately inform the organizations concerned of

the spillage to prevent possible accidents and spreading of spillage. Remove nearly potential ignition sources immediately and make fire-extinguishing agents available. Remove spillage completely, and

ventilate and clean the site and the surroundings.

SECTION 7. Handling and storage

Handling

Technical Measures: Keep away from any possible contact with sparks, open flames, and

high-temperature materials, and do not allow release of vapor without

justification.

Use pump or other proper equipment for taking out from containers.

Do not siphon with your mouth using a tube. Do not drink.

When mist is generated, use respiratory equipment to prevent inhalation

of mist.

In case of vapor / mist dispersion, install a closed system, local ventilation system, and / or other proper equipment for the sources of vapor / mist

generation.

Avoid rough handling of containers such as falling, dropping, exposing

to shock, and dragging.

Ventilation requirements: Maintain adequate ventilation when handling indoors.

Precautions: Wash hands and face thoroughly after handling.

Be careful with fire.

Precautions for safe Av

handling:

Avoid falling, dropping, exposing to shock, or dragging of containers.

Wear protective gloves when opening containers to eliminate a risk of

hand injury.

Storage

Storage Conditions: Store in a well ventilated, cool, dry, dark place, protection from direct

sunlight and keeping away from any potential ignition sources and

high-temperature materials.

Store tightly stopped after use to prevent possible contamination with

dust and moisture.

Preferably store locked up in a proper storage area.

Safety adequate

container materials:

Use spill-proof containers that are free of damage / corrosion.

SECTION 8. Exposure controls/personal protection

Appropriate engineering In case of mist generation, enclose the source of mist generation, or

controls: install a ventilation system.

Install eye cleaning and body cleaning and body cleaning equipment

near the handling site.

Exposure Limits Not established

Allowable Limits: When mists/ aerosols may occur, the following are recommended

5 mg/m³ ACGIH TLV as for mineral oil mist⁽²⁾
10mg/m³ ACGIH STEL as for mineral oil mist⁽²⁾

Personal Protective Equipment

Respiratory Protection: Not needed under normal conditions, but wear a gas mask (against

organic gases) whenever required.

Hand protection: In case of prolonged or repeated exposure, wear oil-resistant hand

protection.

Eye / face protection: In case of exposure to splashes, wear ordinary type goggles.

Skin protection: In case of handling over a prolonged period of time or in case of

exposure to oil, wear oil-resistant, long-sleeved work clothing.

Hygiene Measures: Take off contaminated clothing and wash thoroughly before reuse.

Wash hands thoroughly after handling.

SECTION 9. Physical and chemical properties

Physical state:

Form: Liquid
Color: Brown
Odor: Slight odor
Melting point / freezing point: No data

Initial boiling point and boiling range: Initial boiling point - End point No data

Flash point: 258°C(COC)
Auto-ignition temperature: No data
Upper / lower flammability Explosion (1-7%)

Limit or explosive limits:

Vapour density: No data

Density: 0.86g/cm³(15°C)
Solubility: water: Insoluble

Partition coefficient: No data

Kinematic Viscosity: 90.2mm²/s(40°C)

n-Octanol / water: No data

Decomposition Temperature: No data

Pour point: $\leq -30.0^{\circ}$ C

SECTION 10. Stability and reactivity

Chemical stability: Stable when stored or preserved in a dark place at room temperature. Possibility of hazardous reaction: Keep away from any possible contact with strong oxidizing agents.

Conditions to avoid: Contact with incompatible hazard substances.

Prolonged heating, open flames, and ignition sources.

Incompatible materials: Use care to keep away from any possible contact with halogens, strong

acids, alkalis, and acidifying substances.

Hazardous decomposition When burnt, may release carbon monoxide and other gases.

products:

SECTION 11. Toxicological information

Acute toxicity:

Oral Product: Classification not possible

Mineral oil: Oral LD50 (Rat) >5000mg/kg

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Dermal Product: Classification not possible

> Mineral oil: Dermal(Rat) >5000mg/kg

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Inhalation-mist Product: Classification not possible

> Mineral oil: No data

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Skin corrosion/irritation: Product: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Serious eye damage/ Product: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Respiratory or Skin

Product: Respiratory: Classification not possible Sensitization:

Skin: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Germ cell mutagenicity: Product: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Carcinogenicity: Product: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Reproductive toxicity: Product: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Specific target organ

toxicity

Product: Classification not possible

(Single exposure): For mixtures, hazard category was identified based on the classification criteria for mixtures.

Specific target organ

toxicity

Product: Classification not possible

(Repeated exposure): For mixtures, hazard category was identified based on the classification criteria for mixtures.

Aspiration toxicity: No classification

SECTION 12. Ecological information

Ecotoxicity: About petroleum distillates similar to this mineral oil, there is the following

data(obtained in water accommodated fraction);

Verity BIKE FS HR Ver3 10W-40 MA

Fish Primephales promelas,96hrs, LL50 > 100mg/L Fish Primephales promelas,14days, NOEL > 100mg/L

Crustacea Daphnia magna ,48hrs, EL50/NOEL >10000mg/L

Crustacea Daphnia magna ,21days, NOEL >10mg/L
Algae Selenastrum, NOEL > 100mg/L

Hazardous to the Aquatic Environment

Acute aquatic hazard: Product: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Chronic aquatic hazarc Product: Classification not possible

For mixtures, hazard category was identified based on the classification criteria for mixtures.

Persistence and degradability: Product: No data

Bioaccumutive potential: Product: No data

Mobility in soil : Product: No data

Layer: the Montreal Protocol.

SECTION 13. Disposal considerations

Disposal methods: Dispose of contents / container in accordance with local / regional /

national / international regulations.

Every customer / user of the product should dispose of industrial waste

on its own responsibility, otherwise it must rely on a company

authorized by prefectural governor for treating industrial waste or a local public body involved in the disposal of industrial waste for proper disposal.

Before disposal of used container, remove contents completely.

SECTION 14. Transport information

UN Classification

UN number: Not applicable
UN Class: Not applicable
Package Code: Not applicable

IMDG(SEA): Not applicable IATA(AIR): Not applicable

Specific security precaution and condition of transportation:

Transport containers without causing any significant friction or shaking.

SECTION 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Verity BIKE FS HR Ver3 10W-40 MA

National regulations(Japan)

Fire Service Law: Category 4th, Flammable Liquids, Class #4 Petroleum,

Water immiscible

Industrial Safety and Health Law:

No.57 Law Substance to display: Mineral oil

No.57 Law Substance to notify: Mineral oil, Molybdenum and its compounds.

Pollution Release and Not regulated

Transfer Register(PRTR):

Poisonous & Deleterious Not regulated

Substance Control Act:

SECTION 16. Other information

[References]

- 1. Advice on Allowable concentration, Japan Society for Occupational Health(2018)
- 2. Thresholds limit values for chemical substances and physical agents and biological exposure indices, ACGIH (2010)
- 3. ECHA (European Chemicals Agency), website "ECHA CHEM", Information on Registered Substances (2011). SDS of EU suppliers (2011)
- 4. IARC Monographs Programmed on the Evaluation of Carcinogenic Risk to Humans (2006)
- 5. Globally Harmonized System of Classification and Labelling of Chemicals(GHS):Rev.6(2015)
- 6. SDS provided by the manufacturer.

The information and recommendation provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information and recommendation given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. It is the user's responsibility that the product is suitable for the intended use and the responsibility to insure proper health, safety and other necessary information is included with and/or on the container.