



www.cnlube.co.kr

New Technology Resources

Special Lubricants Oil & Grease

182, Hwasan-ro, Onsan-eup, Ulju-gun, Ulsan City, KOREA

TEL 82-52-239-5189 FAX 82-52-239-5105

e-mail : adm@cnlube.co.kr

Certification Of Analysis

Customer **INDIVIDUAL ENTREPRENUER** Date **24-Aug-22**
 Product **EAGLE PEGASUS MULTI ATF** Lot. No. **22081925**

Test Item	Test Method	Spec.	Results
Apearance	Visual	Red Clear Fluid	Red Clear Fluid
Density (15°C), kg/m³	ASTM D 287	Report	845.7
Viscosity, 100°C, mm²/s	ASTM D 445	Min. 5.5	6.442
Viscosity Index	ASTM D 2270	Min. 90	153
Flash Point(C.O.C, °C)	ASTM D 92	Min. 170	222
Pour Point(°C)	ASTM D 97	Max. -39	- 51
Foaming Characteristics (ml)	Sequence I	ASTM D 892	100 / 0
	Sequence II		100 / 0
	Sequence III		100 / 0
Rust Preventive (Distilled Water, 24hr)	ASTM D 665	Pass	Pass

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. H. Lee

