C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-eup, UlJu-gun, Ulsan, KOREA 45009
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification Of Analysis

Customer INDIVIDUAL ENTREPRENUER **D a t e** 14-Jul-22

Product SCORPION Gear Oil Semi-Syn API GL-4 75W-90 **Lot. No.** 22071228

Test Item		Test Method	Spec.	Results
Appearance		Visual	Clear & Bright	C & B
Density(15℃), kg/㎥		ASTM D 287	Report	846.9
Kinematic Viscosity(100℃), ㎟/s		ASTM D 445	13.5 ~ 24.0	15.99
Viscosity Index		ASTM D 2270	85 min.	155
Flash Point (Open cup method, ℃)		ASTM D 92	180 min.	238
Pour Point, ℃		ASTM D 97	-24 max.	-45
Copper Corrosion (100℃, 3h)		ASTM D 130	1 max	1b
Foaming Charcdteristies, ㎖	Sequence Ⅰ	ASTM D 892	20 / 0	0 / 0
	Sequence Ⅱ	ASTM D 892	50 / 0	10 / 0
	Sequence Ⅲ	ASTM D 892	20 / 0	0 / 0

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. H. Lee