



C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, UJU-kun, Ulsan, KOREA, 45009
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer **INDIVIDUAL ENTREPRENUER** **D a t e** **22-Aug-22**
Product **EAGLE Gasoline Semi-Synthetic 5W30 API SL** **Lot. No.** **22081921**

Test Item		Test Method	Spec.	Results
Appearance		Visual	Clear & Bright	C & B
Density(15°C), kg/m ³		ASTM D 287	Report	856.9
Kinematic Viscosity(100°C), mm ² /s		ASTM D 445	9.3 ~ 12.5	10.45
Viscosity Index		ASTM D 2270	85 min.	154
Low Temperature Cranking Viscosity(-30 °C), Pa·s		ASTM D 5293	6.6 max.	5.25
Flash Point, °C		ASTM D 92	190 min.	226
Pour Point, °C		ASTM D 97	-30 max.	-42
Oxidation Stability (165.5°C, 24hr)	Viscosity Change Ratio	JIS K 2514	1.5 max.	0.98
	TAN Change ,mgKOH/g		1.6 max.	0.31
	Lacquer		Thin	Nil

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager J. H. Lee

