C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-eup, UlJu-gun, Ulsan, KOREA 45009
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer **INDIVIDUAL ENTREPRENUER** **D a t e** **18-Jun-22**

Product **EAGLE PAO 100 SP C3 0W/40** **Lot. No.** **22061727**

Test Item		Test Method	Spec.	Results
Appearance		Visual	Clear & Bright	C & B
Density(15℃), kg/㎥		ASTM D 287	Report	845.8
Kinematic Viscosity(100℃), ㎟/s		ASTM D 445	12.5 ~ 16.3	13.6
Viscosity Index		ASTM D 2270	85 min.	192
Flash Point, ℃		ASTM D 92	195 min.	222
Pour Point, ℃		ASTM D 97	-36 max.	-57
Apparent Viscosity(-35℃), Pa.S		ASTM D 5293	6.2 max.	4.50
Oxidation Stability (165.5℃, 24hr)	Viscosity Change Ratio	JIS K 2514	1.5 max.	0.98
	TAN Change ,㎎KOH/g		1.6 max.	0.33
	Lacquer		Thin	Nil

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center

Manager **J. H. Lee**