

X1 5W40

ESTER HYBRID SYNTHETIC MOTOR OIL

DESCRIPTION

Ester based synthetic high performance engine oil that provides optimum protection and extended engine life and reliability. It exceeds the performance requirements of virtually all engine manufacturers. Combines exceptional anti-wear performance and outstanding high temperature protection with excellent cold start characteristics.

PROPERTIES

- Reduced fuel consumption and CO₂ emissions.
- Helps to deliver important boost in engine power.
- High and very stable viscosity index.
- Fast cold start.
- Delivers superior thermal stability, ensuring minimal engine deposits for cleaner internals.
- Ensures engine protection from the first moment of ignition, minimizing wear and damage.
- Protects Diesel Particle Filters.



APPLICATION

Suitable for both turbocharged and normally aspirated petrol & diesel engines. Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.

TYPICALS

Density at 15 °C, kg/l	0,850
Viscosity -30 °C, mPa.s	6010
Viscosity 40 °C, mm ² /s	83,40
Viscosity 100 °C, mm ² /s	13,90
Viscosity Index	171
Flash Point COC, °C	246
Pour Point, °C	-39
Total Base Number, mgKOH/g	7,4

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
60 L drum
208 L drum

SPECIFICATIONS

ACEA C3-12
API SN/CF

Meets the requirements of
VW 502.00/505.00/505.01
MB 229.31/226.5
BMW Longlife-04
Ford M2C917-A
Porsche A40
Renault RN0700/RN0710
Dexos 2

Previously classified & applicable also:
ACEA A3/B4-04